

# Rapidlogger™

## Rapidlogger Wellhead Monitor System



When used in the artificial lift mode, the system can monitor and control pump jack or ESP speeds in addition to monitoring the standard production parameters. With a lift optimization schedule available the system can follow it to maximize production volume or balance pipeline capacity.

### Technical Specifications:

Dimensions	70 x 20 x 19 inch
Operating Temperature	-20C to 60C
Enclosure Rating	IP67, NEMA 6
Power In	9-36VDC, 120VAC
	100W solar panel
Backup Capacity	1.2 to 16 Ah
Battery Specs	10+yrs float life @25C avg 5+yrs float life @35C avg 500cycle @ 80% disch 2500cycle @ 30% disch high pressure cells
Job Memory	4GB minimum

**Part Number**

**00-93653**

### Applications

The Rapidlogger Wellhead Monitor is a self-contained state-of-the-art system for monitoring and recording data on wellheads. The system can be supplied configured for remote transmission over wired networks, cellular or satellite networks. The Rapidlogger system is very power efficient and requires very low power. This makes the system very suitable for operation from solar panels. This is a big advantage for locations without power, and where solar power is the only option. The system has been specifically designed from the ground up for continuous use in extremely hot or cold environments without failure.

#### *Production Monitoring Mode:*

When used in the production monitoring mode the system can monitor, display and record parameters like: wellhead pressure, production flow-rate, temperature, and tank level. Additional parameters can be selected, monitored and recorded. The unit can be networked for centralized monitoring and control or transmit its data over a cellular or satellite telephone link.

#### *Artificial Lift Mode:*

